




Note:

- \* RoHS Compliant
- \*  Important dimension
- \*  Waterproof rate: IP68, mated 1m/24h  
IP69K, mated
- \* Connector
  - Housing: Thermoplastic, Black
  - Pin: Copper alloy, Gold plated
  - O-Ring: Rubber, Green
  - Nut: Metal
  - Outer mold: Thermoplastic, Black
- \* Cable: IEC61156-12, 26#\*IP+AL/MY+B, OD=3.8mm,  
PUR Jacket, Green
- \* Cable length tolerance: 1M: +50/-0 mm
  - 1M < L ≤ 3M: +100/-0 mm
  - 3M < L ≤ 5M: +150/-0 mm
  - 5M < L ≤ 10M: ±100 mm
  - 10M < L ≤ 15M: ±200 mm

		
2Pin		
3	White	白
1	Blue	藍
Pin#	Wire	
Pin Assignments		
Front View		

UNIT: mm		TITLE N SEN, MI2 A, SCREW CABLE W/O SR, F, F, MOLDING			<h1>Amphenol LTW</h1> <h2>安費諾亮泰企業股份有限公司</h2>	ITEM NO	DRAWN BY Allen Pan	DATE 2021-08-27
TOLERANCE		SCALE 3:2	SIZE A4	SHEET 1 OF 1		DWG NO MI2A-XXBFFM-SL8CXX	CHECKED BY Sam Ho	DATE 2021-08-27
±0.5mm		REV. B	WC-REV. A.1	QC: Inspection item		CUSTOMER ALTW	APPROVED BY Fred Lee	DATE 2021-08-27