REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2013/05/21	Doreen	Change REV.01 to REV.A
B	C231296	2023/10/12	Vicky	△B X2













Conn.
Pin Assignments
Front View

Note:
* QC Important Dimension To Check.
* Waterproof Rate : IP67
* Connector: PPE, Black
* Female Pin:Copper Alloy,Tin Plated
* Current Rating: 30A(Max.)
* Rated Voltage:300V
* Recommended Gauge: 8awg~14awg
* Nut: PPE, Black
* O-Ring & Gasket:Silicone, Gary
* Cable OD Max: Bl:Ø10~Ø14.5mm
△B * One set unassembled in one pe bag

UNIT:mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: PWR, LED 30A, CABLE W/O SR F, F, FI SOLDER, 3LOCK △B

SCALE 1:1 | SIZE A4 | SHEET 1 OF 1

REV. B | WC-REV. A.3 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO: PWL-03BFFA-TL7002	DRAWN BY: Doreen	DATE: 2013/05/21
DWG NO: PWL-03BFFA-TL7002	CHECKED BY: Nick	DATE: 2013/05/21
CUSTOMER: ALTW	APPROVED BY: Denys	DATE: 2013/05/21

W10814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY LTW.