

X-Lok Connectors

1 — 2 3 4 5 6 — 7 8 9 10

Specification / Current Rating
(SCC) 20A

Number of Contacts

03
EX. (03) = 3 Contacts

Connector Body (Style)

> For Receptacle (R) Rear Fastened	> For Overmolded with Cable (M) With Strain Relief	> For Field installable (F) Without Strain Relief
---------------------------------------	---	--

Connector (Housing) Gender

(M) Male Connector (F) Female Connector

Contact Gender

(S) Male (Stamp)
(P) Female (Stamp)

Assemble Style

> For Receptacle (S) Solder Type	> For Overmolded with Cable (S) Solder Type > For Field Installable (C) Crimp Type
-------------------------------------	---

Mating Style

(Q)-Push Lock (X lok)

Backshell

> For Receptacle (C) Circular	> For Overmolded with Cable (L) Straight (R) Right Angle (Avaible soon)	> For Field Installable (L) Straight
----------------------------------	---	---

Waterproof Rating

(7) IP 67

More information

> For Receptacle (001), (002)..... Without Cable : Different Versions	> For Overmolded with Cable (□)+(■) : Cable Type + Cable Length EX. (A01) = UL2464 Cable + 1M (□) : Cable Type (■) : Cable Length (A) UL2464 Cable From 1M to 99M (B) UL2586 Cable EX. (01) = 1M (C) Power Cable(TC-ER)
--	---