

IEEE 1394 Connectors



Specification

(13) 1394 Connector

Type

(AA) 1394A

Connector Body (Style)

> For Receptacle	> For Overmolded with Cable
(P) Front Fastened	(A) With Strain Relief
> For Field installable	(B) Without Strain Relief
(B) Without Strain Relief	

Connector (Housing) Gender

(M) Male Connector	(F) Female Connector
--------------------	----------------------

Contact Gender

(M) Male (Plug)	(F) Female (Jack)
-----------------	-------------------

Assemble Style

> For Receptacle	> For Overmolded with Cable
(P) 180° PCB Type	(M) Overmolded with Cable
	> For Field Installable
	(A) Field installable (Solder)

Mating Style

(S) Screw Thread

Backshell

> For Receptacle	> For Overmolded with Cable
(C) Circular	(L) Straight
> For Field Installable	
(L) Straight	

Waterproof Rating

(7) IP 67
(8) IP 68

More Information

> For Receptacle	> For Overmolded with Cable
(001) Without Cable	(□)+(■) : Cable Type + Cable Length
(002) With Cable (Harness (50mm))	EX. (A01) = 1394A Cable + 1M
	(□) : Cable Type (■) : Cable Length
	(A) 1394A Cable From 1M to 4M
	EX. (01) = 1M