

Product Range Overview

Sub-Series Name	Circular	Rectangular	Mini-HDMI*
Mating Style	Screw Thread	Push Lock With Latch	Screw Thread
Metal Version	-	✓	-
No. of Contacts	19	19	19
Plating of Contacts	Gold Plated	Gold Plated	Gold Plated
Operating Voltage	30V AC	30V AC	30V AC
Current Rating	0.5A	0.5A	0.5A
Operating Temperature	<ul style="list-style-type: none"> • Receptacle: -20°C ~ 80°C • Overmolded with Cable: -20°C ~ 80°C 		
Fasten Style of Nut	Front	Front	Front
Receptacle	✓	✓	✓
Overmolded With Cable	✓	✓	✓
Accessories	✓	✓	✓
Applicable Wire Gauge	26AWG (0.14mm ²)	26AWG (0.14mm ²)	30AWG (0.05mm ²)
Mating Cycles	500 Cycles	500 Cycles	500 Cycles
IP Rating	<ul style="list-style-type: none"> • Receptacle: IP67 (Unmated) • Overmolded With Cable & Field Installable: IP67 (Mated) 		
Salt Spray	48h	48h	48h
Vibration	Frequency Range 10~55Hz Amplitude 1.52mm		
RoHS 2.0 Compliant	✓	✓	✓
REACH Compliant	✓	✓	✓

*Upon request